

How to do Subcycled, Self-Gravitating Hydrodynamics on an Adaptive Mesh: Essential Obstacles and Fundamental Methodology

R. Fisher, R. Klein, L. Howell, J. Greenough, C. McKea

This article was submitted to *AMR Workshop, Chicago, II*
September 4th, 2003

U.S. Department of Energy

Lawrence
Livermore
National
Laboratory

August 26, 2003

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

This work was performed under the auspices of the United States Department of Energy by the University of California, Lawrence Livermore National Laboratory under contract No. W-7405-Eng-48.

This report has been reproduced directly from the best available copy.

Available electronically at <http://www.doc.gov/bridge>

Available for a processing fee to U.S. Department of Energy
And its contractors in paper from
U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
Telephone: (865) 576-8401
Facsimile: (865) 576-5728
E-mail: reports@adonis.osti.gov

Available for the sale to the public from
U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
Telephone: (800) 553-6847
Facsimile: (703) 605-6900
E-mail: orders@ntis.fedworld.gov
Online ordering: <http://www.ntis.gov/ordering.htm>

OR

Lawrence Livermore National Laboratory
Technical Information Department's Digital Library
<http://www.llnl.gov/tid/Library.html>

How to do subcycled, self-gravitating

hydrodynamics on an adaptive mesh:

essential obstacles

and fundamental methodology

Robert Fisher (LLNL)

Richard Klein (LLNL/UCB)

Louis Howell (LLNL)

Jeff Greenough (LLNL)

Christopher McKee (UCB)

AMR Workshop

ASCI Flash Center

9/4/2003

Overview

- Fundamental equations
- AMR Background: Hydrodynamics
- Option 1: Dirichlet BCS
- Option 2: Neumann BCS
- Test Results

Fundamental Equations


$$\frac{\partial \rho}{\partial t} + \vec{\nabla} \cdot (\rho \vec{v}) = 0$$

$$\frac{\partial (\rho \vec{v})}{\partial t} + \vec{\nabla} \cdot (\rho \vec{v} \vec{v}) = -\vec{\nabla} P - \rho \vec{\nabla} \Phi$$

$$\vec{\nabla}^2 \Phi = 4\pi G \rho$$

$$P = (\gamma - 1) \rho \epsilon_{\text{int}} \quad \left. \vphantom{P = (\gamma - 1) \rho \epsilon_{\text{int}}} \right\} \text{ in this work}$$

AMR Background: Hydrodynamics



- 1) Advance level 0 at timestep Δt_0 .
- 2) Advance level 1 at timestep $\Delta t_1 = \Delta t_0 / \text{ref}$.
 - Use time- and space-interpolated values for ghost cells on $\partial(L_1)$.


- 3) Coarsen down L_1 data onto L_0 .
- 4) Correct for flux mismatches via refluxing.

Option 1: Dirichlet bcs.

Assign $\Phi(\vec{x}, t)$ on grid boundaries using Dirichlet.

$$\Phi(\vec{x}, t) = \xi(\vec{x}, t) \left\{ \text{where } \vec{x} \in \partial(L1) \right.$$

$\Rightarrow \Phi$ continuous, $\vec{\nabla} \Phi$ not.




$$\vec{n} \cdot (\vec{g}_{x,0} - \vec{g}_{x,1}) = -4\pi G \Sigma$$

Option 2: Neumann bcs

Assign $\vec{\nabla}\Phi(\vec{x}, t)$ on grid boundaries using Neumann.

$$\vec{\nabla}\Phi(\vec{x}, t) = \vec{g}(\vec{x}, t) \quad \left\} \text{ where } \vec{x} \in \partial(L_1)\right.$$

$\Rightarrow \vec{\nabla}\Phi$ continuous, Φ not.



$$\int_A \vec{g} \cdot d\vec{A} = 4\pi G M_{\text{enclosed}}$$

Algorithm

104

If ($l < l_{max}$) and (regrid requested for timestep n) Then

For $l' \in \{l_{max} - 1, \dots, l\}$ do

- Determine new grid layout for level $l' + 1$.
- Interpolate data to new grids from level l' .
- Copy data on intersection with old level $l' + 1$ grids.

End do

If ($l < l_{max}$ or $t^{old,l} = t^{old,l-1}$) then

On $\partial\Omega^l$ and $P(\partial\Omega^{l+1})$:

- Store $F_{rad}^{l,n}$ and $\vec{g}^{l,n} = -\nabla\Phi^{l,n}$ in registers.

On Ω^l :

- Compute $\nabla^2\Phi^{l,n}$ and $\nabla \cdot F_{rad}^{l,n}$.

Endif

Level Time Step, level l :

- Multi-Fluid Explicit Godunov Hydrodynamic Update
- FLD Radiative Level Solution and Implicit Energy Update
- Poisson Level Solution and Explicit Momentum and Energy Update

End Level Time Step

If $l < l_{max}$ then

FLD Radiation Multilevel Solve: $l' \in l, \dots, l_{max}$

Poisson Multilevel Solve: $l' \in l, \dots, l_{max}$ (Solve for Φ_{corr} and \vec{g}_{corr})

- $D^{E \rightarrow C}(\vec{G}^{C \rightarrow E}\Phi_{corr}) = \tilde{D}^{E \rightarrow C}(\delta\vec{g}^{l+1,n+\theta})$

- $\vec{g}_{corr} = -\vec{G}^{C \rightarrow C} \Phi_{corr}$

End Poisson Multilevel Solve


For $l' \in l_{max}, \dots, l$ do

On $\Omega^{l'+1} - P(\Omega^{l'+1})$:

- $(\rho \vec{v})^{l',n+1} = (\rho \vec{v})^{l',n+1} + \rho^{l',n+1} \vec{g}_{corr}^{l',n+1} \Delta t^{l'}$
- $\Phi^{l',n+1} = \Phi^{l',n+1} + \Phi_{corr}^{l',n+1}$

End do

Test Problems




$$\chi_p = \rho_0 / \rho_{amb}$$

$$\chi_p = \rho_0 / \rho_{amb}$$

$$\alpha = \frac{\text{thermal energy}}{|\text{gravitational energy}|}$$

$$B = \frac{\text{rotational energy}}{|\text{gravitational energy}|}$$






FIG. 5.—Equatorial slice of log density in the uniform collapse problem. At the time shown, about half of the cloud mass, gas inside the central plateau in this figure, remains undisturbed by the inward-moving rarefaction wave.


the result that the grids form simple cubes about the cloud. Tracing a radial line, we therefore first encounter decreased resolution along the coordinate axes; this is clearly visible in Figure 5. Because the gradient is most poorly resolved at these points, the volume averaging of the highest density gas just outside the finer grid is most approximate at these six (in three dimensions) cloud-grid tangent points. This, too, can be seen in the Figure 5 as distinct (though slight) overdense regions (relative to gas at the same radii) at these points in the equatorial plane. An increase in χ_p leads to an increase in the rate of expansion of the surface layers of the cloud and a hastened reduction of the steep gradient, resulting in a lowering of the effective χ_p . We found that use of $\chi_p = 10$ reduced the bump amplitude relative to the plateau by 40% in the log when compared to the $\chi_p = 1$ run at the same $\rho_{\text{max}} = 10^{-11.6} \text{ g cm}^{-3}$. In runs of uniform clouds with more astrophysically realistic energy ratios α and β_Ω , such as the remainder of the uniform clouds considered in this paper, we did not find this edge effect to be of importance. An increase in either could be expected to damp the perturbations. We conclude that it is a numerical artifact of little practical significance and is realized only at the extremely low α and β_Ω of this problem. It does, however,

8/19/2003


1

$\Sigma = 1/8$, R_{64} Cold Uniform Collapse
Refinement Factor 2

$$t = 6.51399 \times 10^{10} \text{ s} = .9805 \text{ yr}$$



Further Considerations



$$\begin{aligned}
 4\pi G \Sigma &= \left(-\vec{\nabla} \varphi_0 + \vec{\nabla} \varphi_1 \right)_{r=R} = -\vec{\nabla} \left(-\frac{G \vec{p} \cdot \vec{r}}{r^2} \right)_{r=R} \\
 &= \left(-\frac{2Gm d \cos \theta}{r^3} \right)_{r=R} = \frac{-2Gm d \cos \theta}{R^3}
 \end{aligned}$$

$$\Sigma = \frac{-m}{2\pi} \frac{d}{R^3} (\cos \theta)$$